

Ravo 540 STH



Accessoires

- Airconditioning
- Anti-lock braking system
- Euro 6
- Radio/CD player
- Rental sweeper
- Warning lights

| | |
|----------------|--------------------------|
| ID number | 40174 |
| License plate | TK-X0-6S |
| Mileage | 37169 |
| Year | 2020 |
| Chassis number | XM45F6HB1LA020110 |
| Fuel | Diesel |
| Euro norm | Euro 6 |
| Transmission | Automatic |

Price on request

Comments

- Euro 6 diesel engine.
- Rotating beacons mounted on the cab and the tailgate.
- Daytime running lights and rear lights in LED version.
- Brush lighting left and right.
- Squeegee lighting.
- Four large mirrors.
- Sidewalk mirrors left and right.
- Rear view camera, with monitor in the cabin.
- 2-speed windscreen wipers with adjustable interval.
- Steering column adjustable in angle and axially.
- Flat mounted window in the floor for a view of the nozzle.
- Powerful heating with integrated air conditioning.
- Mechanically suspended driver's seat with 2-point safety belt.
- Passenger seat with 2-point safety belt.
- Adjustable right armrest with raised edge.
- Step steps on the brush arms.
- Multi-functional display of RAVO-iSystem in the cabin, for reading many vehicle data.
- Radio with USB connection and 2 speakers.
- Adjustable center console with controls and storage.
- 12 V connection in the cabin.
- Pen tray with cup holders between the seats.
- Storage compartment with flap on the left above the windscreen.
- Emergency stop in the cabin.
- Tool case.
- Fire extinguisher.
- Squeegee covered with durable material.
- Suspension wheel on the nozzle.
- Extra connection water system for self-cleaning impeller and impeller housing.
- 2 round reflectors on the rear of the chassis.
- Stainless steel hooks on the service doors.
- Electronic parts book on USB stick.

- Extra hydraulic brush angle adjustment on the third trough brush.
- Covering the suction pipe with wear-resistant material.
- Covering the suction pipe bend with wear-resistant material.
- Covering the suction pipe connection container with wear-resistant material.
- Covering the deflector plate with wear-resistant material.
- Boron impeller instead of the standard aluminum impeller.
- High pressure water pump, incl. Spray gun and a self-winding reel with 10 m.
- Spray gun is stored on the right side of the container. Capacity: 15 l / min, m.

General

| | |
|---------------------|-----------------|
| Dimensions | 580 x 210 x 260 |
| Overall condition | Excellent |
| Technical condition | Excellent |
| Optical condition | Excellent |

Chassis

| | |
|-----------------------|-------|
| Own weight (kg) | - |
| Loading capacity (kg) | - |
| GVW (kg) | 11400 |
| Wheelbase (kg) | 180 |

Powertrain

| | |
|------------------------|-----------|
| Transmission | Automatic |
| Cylinder capacity (cc) | - |
| Engine power (pk) | - |
| Engine power (kw) | - |

Axle configuration (4x2)

| | | |
|--------------------|-------------|-----------|
| Tire size | 215/75R17.5 | 355/45R15 |
| Profile Left/Right | / | / |
| Suspension | Hydraulic | Hydraulic |
| Maximum axle load | 4850 | 7070 |
| Reduction | - | - |
| Axle lift | ✘ | ✘ |
| Steering | ✓ | ✘ |
| Powered | ✘ | ✓ |

All prices are excluding VAT

All specifications are subject to change. The given mileage, sizes, weights and other specifications are not legally binding